

BA-88A

Semi-Auto Chemistry Analyzer

- Endpoint , Fixed-time , Kinetics and Absorbance
- Wavelengths range 340 to 670nm
- 7 . 0 " TFT touch screen & popup keypad
- External keyboard and mouse support via USB
- Up to 200 tests can be programmed
- Testing modes: flowcell and cuvette
- User-friendly interface
- Power-failure protection
- Universal power supply




BA-88A

Semi-Auto Chemistry Analyzer


Straightforward software interface, easy to get started!

Large LCD touch-screen, clear and user-friendly


Two USB ports (2.0), for keyboard, mouse, printer




- Simple parameters setup
- Quick interchange between 4 temperature options
- Support Bi-Chromatic tests



- Multi-functional and comprehensive testing panel interface display
- Real-time monitor of reaction curve/data and temperature change
- Parameters can be reviewed in test panel



- Customizable patient information
- Capable of adding off-system test results



- Support K-factor programming

Support two testing modes: Flowcell or Cuvette; easy to shift between modes

Easy maintenance: remove black cover to change lamp



BA-88A

Semi-Auto Chemistry Analyzer

Technical Specifications:

Principles

ALT, AST, ALP, ACP, GGT, α-HBDH, LDH, CK, AMY, TG, TC, HDL-C, UA, UREA, Cr, Glu, TP, Alb, T-Bil, TBA, NH4+, HCO3-, Ca, Mg, Cl, Na, K, apoA1, apoB, Lp (a), C3, C4, IgG, IgA, IgM, HbA1c, Alcohol, Amphetamines, Barbiturates, Benzodiazepine etc.

Analysis Method

Endpoint, with or without reagent blank
Endpoint, with sample blank and reagent blank
Kinetics, with or without reagent blank
Two-point Kinetics/Fixed-time, with or without reagent blank
Absorbance
Turbidimetry
Linear and non-linear calibration

Light Source

Tungsten-halogen lamp 6V/10W

Wavelength Range

Automatic by 8-position filter wheel
8 standard filters : 340nm, 405nm, 450nm, 510nm, 546nm, 578nm, 630nm and 670nm. Bandwidth < 8nm
Stray light : < 0.1% @ 340nm

Photometric Range

0~3.5 ABS
Stability : < 0.005A / 20min @ 340nm

Flowcell

Stainless steel with quartz window
Measuring volume : 32 µL
Optical path : 10mm
Aspiration volume programmable : 200~9000 µL

Input

Touch screen with touch pen and popup keypad
Mouse or Keyboard via USB

Temperature Control

By means of Peltier elements
Room temperature, 25°C, 30°C and 37°C

Storage

More than 3000 sample results
More than 1000 QC results

Printer

Built-in thermal printer
Support HP series

Interface

RS232 serial port supporting data transmission
USB port (2.0) for keyboard, mouse, printer

Operating Environment

Temperature : 15°C~30°C
Humidity : 35%~85%, no condensation

Power Requirement

Wide power supply : AC 100-240V, 50 / 60Hz

Dimension

430mm x 360mm x 170mm (L x W x H)

Weight

6.8 Kg